

Ramonol Advanced

A superior white calcium sulphonate grease with anti-sheen properties

Application

Suitable for use in all conventional grease applicators. Especially suitable for stern gland and steering glands, bearings, seacocks, winches, furling gears, propellers, engine controls and levers, all types of bearings and general greasing where the highest level of protection is required. It is also suitable for lubricating and protecting steel and aluminium wires in a marine environment with no discernible sheen.

Properties

Ramonol Advanced is an exceptionally high quality multi-purpose grease formulated with a high drop point calcium sulphonate thickener and a special solid lubricant to improve boundary and emergency lubrication. It is highly water resistant to fresh and salt water, has excellent extreme pressure, anti-wear, oxidation resistance and adhesive properties, making it ideally suited for the harshest marine applications.

Characteristics

Product code		68285
Base oil nature	-	Mineral
Thickener type	-	Calcium sulphonate
Colour	-	White
Penetration 60W, 25°C	mm	285-315
NLGI Consistency Class	-	1-2
Drop point (minimum)	°C	270
EMCOR corrosion test- salt water	-	0
Water washout 80°C	%	2 max
Salt spray chamber min 300 hours	-	1
Copper corrosion 24hr/100°C	-	1b
4 ball weld load	Kg	500 min
Working temperature range	°C	-30 to 175+

All values are typical and there may be batch variations.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

Availability 500g plastic tub, 78g tube with applicator, 400g cartridge, 12.5kg or 18kg pails and 185kg drums.

Gruebb Ltd, 29 Carlton Crescent, Southampton, SO15 2EW, England
Company number 3954831 Tel : + 44 (0)2380 089084 Fax : +44 (0)2380 335784