

SAFETY DATA SHEET

Report No.: CMC231117055M01

Name of sample: Rechargeable Li-ion Cell

Model: 704159P

Type: 3.7V 2000mAh 7.4Wh

Client: Dongguan Golden CEL Battery Co., Ltd.

Address: No.11, Yinhu Industrial park, JiaoYiTangManagement Zone, TangXia, DongGuan, GuangDong, P.R. China

Written: Riley Liaw Approved:

Reviewed: // /ail /ou

Date of issue: 2024.01.01 Seal of CMC

CMC Testing International (Shenzhen) Co., Ltd

The supplier identified below generated this SDS using the CMC SDS template. CMC did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. CMC makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS.

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 1 / 15



Safety Data Sheet

Section 1- Identification of the Substance/Preparation and of the Company/Undertaking			
(a) Product identifier			
Name of Sample	Dankannahla Liian Call	Weight	31.7g
Name of Sample	Rechargeable Li-ion Cell	Size (L×W×T)	(59.0×41.0×7.0)mm
Model	704159P		
(b) Other means of identifi	ication		
Synonyms:	None		IKI
(c) Recommended use of	the chemical and restrictions on u	use	
Recommended use:	LITHIUM ION BATTERIES		
Restriction on use:	No information available.		
(d) Details of the supplier	of the product		
Manufacturer	Dongguan Golden CEL Battery Co., Ltd.		
Manufacturer's Address	No.11, Yinhu Industrial park, JiaoYiTangManagement Zone, TangXia, DongGuan, GuangDong, P.R. China		
Contact Person	Mr. Zhi		
E-mail	zhirongjian@celbattery.com		
Telephone:	+86-769-82195308		
Fax:	+86-769-87982226		
(e) Emergency phone number	+86-769-82195308-8016		

Section 2- Hazards Identification

(a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 3
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 2 / 15



Specific target organ toxicity (repeated exposure)	Category 1
Carcinogenicity	Category 2
Skin sensitization	Category 1

(b) GHS Label elements, including precautionary statements

Emergency Overview

Signal word: Danger Hazard Statements

Harmful if swallowed

Causes severe skin burns and eye damage

May cause an allergic skin reaction

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Appearance Silve <mark>r</mark>	Physical State Solid Odor Odorless	
	Obtain special instructions before use	
	Do not handle until all safety precautions have been read and understood	
	Use personal protective equipment as required	
Precautionary Statements-	Wash face, hands and any exposed skin thoroughly after handling	
Prevention	Do not breathe dust/fume/gas/mist/vapors/spray	
	Do not eat, drink or smoke when using this product	
	Contaminated work clothing should not be allowed out of the workplace Wear protective gloves	
	IF EXPOSED OR CONNECTED: Get medical advice/attention. Specific treatment (see supplemental first aid/instruction on this label).	
Precautionary Statements-	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician.	
Response	IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and water before reuse, if skin irritation or rash occurs: get medical advice/attention if feel unwell.	
	IF INHALATION: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing	

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 3 / 15



	respiratory symptoms: Call a poison center or doctor/physician.	
	IF SWALLOWED: Rinse mouth, do not induce vomiting, call a poison center or doctor/physician if feel unwell.	
Precautionary Statements-		
Storage	Store locked up	
Precautionary Statements-		
Disposal	Dispose of contents/container to an approved waste disposal plant	
(c) Hazards not otherwise	Not applicable	
classified (HNOC)	Not applicable	
(d) Unknown Toxicity		
(a) Other information	Very toxic to aquatic life with long lasting effects; Repeated or prolonged	
(e) Other information	skin contact may cause allergic reactions with susceptible persons.	
(f) Interactions with Other Chemicals No information available.		

Section 3- Composition/Information on Ingredients

Chemical Name	CAS Number	Weight-%	Trade Secret
Lithium Cobalt Oxide (LiCoO ₂)	12190-79-3	37.47	*
Graphite	7782-42-5	15.35	*
Copper	7440-50-8	10.36	*
Aluminum foil	7429-90-5	9.25	*
Polyprop <mark>ylene</mark>	9003-07-0	1.54	*
1,1-Difluoroethylene polymer	24937-79-9	1.52	*
Polyethylene	9002-88-4	3.15	*
Styrene-Butadie <mark>ne polymer</mark>	9003-55-8	0.86	*
Carboxymethyl cellulose	9000-11-7	0.74	*
Nickel	7440-02-0	1.34	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	17.49	*
Nylon	24937-16-4	0.93	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.



	Report No.: GMG251117055M01		
Section 4- First Aid Measures			
(a) Description of firs	st aid measures		
General Advice	First aid is upon rupture of sealed battery.		
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.		
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is required. May cause an allergic skin reaction. Remove and isolate contaminated clothing and shoes.		
Inhalation:	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method, if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.		
Ingestion:	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.		
Self-protection of the first aider:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).		
(b) Most important symptoms/effects, acute and delayed			
Most important symptoms and effects:	Itching. Coughing and/ or wheezing. Burning sensation.		
(c) Indication of any	immediate medical attention and special treatment needed		
Notes to Physician	Treat symptomatically. May cause sensitization of susceptible persons.		

Section 5- Fire Fighting Measures			
(a) Extinguishing media			
Suitable extinguishing	ode extinguishing incasares that are appropriate to local circumstances and the		
media:	surrounding environment.		
Unsuitable	CAUTION: Use of water spray when fighting fire may be inefficient.		
extinguishing media:			
(b) Special hazards arising from the chemical			
The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.			
Hazardous	Carbon oxides.		
Combustion Products	Calbuit oxides.		

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 5 / 15



Evaluation Data	Sensitivity to Mechanical Impact:	No.	
Explosion Data	Sensitivity to Static Discharge:	No.	
(c) Special protective equipment and precautions for fire-fighters			
,	, ,		

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental Release Measures				
(a) Personal precaution	(a) Personal precautions, protective equipment and emergency procedures			
Personal Precautions:	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.			
Other Information:	Refer to protective measures listed in Sections 7 and 8.			
(b) Environmental Precautions				
Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.				
(c) Methods and materials for containment and cleaning up				
Methods for Containment	Prevent further leakage or spillage if safe to do so.			
Methods for cleaning up	Pick up and transfer to properly labeled containers.			

Section 7- Handling and Storage			
(a) Precautions fo <mark>r safe handling</mark>			
Handling:	Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.		
(b) Conditions for safe storage, including any incompatibilities			
Storage:	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.		
Incompatible Products:	Acids. Bases. Oxidizing agent.		

Section 8 - Exposure Controls/Personal Protection (a) Control parameters Exposure Guidelines Exposure Guidelines ACGIH TLV OSHA PEL NIOSH IDLH Lithium Cobalt Oxide (LiCoO₂) 12190-79-3

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 6 / 15



Graphite 7782-42-5	TWA:1mg/m³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m³ total dust synthetic TWA: 5 mg/m³ respirable fraction Synthetic (vacated) TWA: 2.5 mg/m³ respirable dust natural (vacated) TWA: 10 mg/m³ total dust synthetic (vacated) TWA: 5 mg/m³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m³ TWA: 2.5 mg/m³ respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA:2.5mg/m³ F	TWA:2.5mg/m³ F TWA:2.5mg/m³ dust (vacated)TWA:2.5mg/m³	
Copper 7440-50-8	TWA:0.2mg/m³ fume TWA:1mg/m³Cu dust and mist	TWA:0.1mg/m³fume TWA:1mg/m³dust and mist (vacated) TWA:0.1mg/m³Cu dust,fume,mist	IDLH:100mg/m³dust ,fume and mist TWA:1mg/m³dust and mist TWA:0.1mg/m³ fume
Aluminum foil 7429-90-5	TWA:1mg/m³ respirable fraction	TWA:15mg/m³ total dust TWA:5mg/m³respirable fraction (vacated) TWA:15mg/m³total dust (vacated) TWA:5mg/m³ respirable fraction(vacated) TWA:5mg/m³ AL Aluminum	TWA:10mg/m³ total dust TWA:5mg/m³ respirable dust
Nickel 7440-02-0	TWA:1.5mg/m³	TWA:1mg/m³ (vacated) TWA:1 mg/m³	IDLH:10mg/m³ TWA:0.015mg/m³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters			
(b) Appropriate en <mark>gineering</mark>	g controls			
	Showers			
Engineering Measur <mark>es</mark>	Eyewash stations			
	Ventilation systems			
(c) Individual protection me	(c) Individual protection measures, such as personal protective equipment.			
Eye/Face Protection:	None required for consumer use. If there is a Hazard of contact:. Tight sealing safety goggles. Face protection shield.			
Skin and Body Protection:	None required for consumer use. If there is a Hazard of contact:. Wear protective gloves and protective clothing.			
Respiratory Protection No protective equipment is needed under normal use conditions. If exposu limits are exceeded or irritation is experienced, ventilation and evacuation makes the required.				



Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. No information available.

Section 9- Physical and Chemical Properties							
(a) Physical State							
Physical state:	À	Solid					
Appearance:	-	Silver pr	rismatic	Odor:		Odorless	
Color:		Silver		Odor Threshold:		No information available	
(b) Chemical Propo	erties	;					
Property			Values		Remarks/ Method		
рН			No data available		None kr	nown	
Melting point/freezing	g poin	t	No data available		None kr	nown	
Initial Boiling Point A	nd Bo	iling	No data available		None kr	None known	
Flash Point			No data available		None known		
Evaporation Rate			No data available		None known		
Flammability (Solid,	Flammability (Solid, Gas)		No data available		None known		
Upper/Lower Flammers			No data available				
Vapor Pressure	1		No data available		None kr	nown	
Vapor Density			No data available		None known		
Relative Density	sity		No data available		None known		
Solubility(les)	ity(les)		Insoluble in water		None known		
Partition Coefficient: N-Octanol/Water	ent:		No data available		None known		
Auto-Ignition Temper	ature		No data available		None known		
Decomposition Temperature		No data available		None known			
Kinematic viscosity			No data available		None kr	nown	
Dynamic viscosity No data a		No data available		None kr	nown		
Explosive properties		No data available					
Oxidizing Properties		No data available					
(c) Other Information							
Softening Point			No data available				
			ı				

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 8 / 15



VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	No data available

Section 10 – Stability and Reactivity		
(a) Reactivity	No data available.	
(b) Chemical stability	Stable under recommended storage conditions.	
(c) Possibility of hazardous reactions	None under normal processing.	
(d) Hazardous polymerization	Hazardous polymerization does not occur.	
(e) Conditions to avoid	None known based on information supplied.	
(f) Hazardous decomposition products	Carbon oxides.	

Section 11 – Toxicological Information					
		kely routes of exposure			
Product Information		Product does not present an ac In case of rupture:	cute toxicity hazard based on kno	own or supplied information.	
Inhalation		Specific test data for the sub of respiratory tract.	Specific test data for the substance or mixture is not available. May cause irritation		
Eye Contact		· · · · · · · · · · · · · · · · · · ·	ostance or mixtu <mark>re is no</mark> t avail s. Irritating to eyes. May caus eye irritation.		
Skin Contact		· · ·	ostance or mixture is not avail urns. May be absorbed throug with skin.		
Ingestion		Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.			
Component Informa	ation				
Chemical Name		Oral LD50	Dermal LD50	Inhalation LC50	
Graphite 7782-42-5		> 10000 mg/kg (Rat)	-	-	
Nickel 7440-02-0	III-	>9000 mg/kg (Rat)	-	-	
(b) Information on toxicological effects					
Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives.					

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 9 / 15



(c) Delayed and im	mediate effects as w	ell as chronic effe	cts from short and lon	g-term exposure	
Sensitization:	May cause sens	May cause sensitization of susceptible persons. May cause sensitization by skin contact.			
Mutagenic Effects:	No information	No information available.			
Carcinogenicity:	The table below carcinogen.	The table below indicates whether each agency has listed any ingredient as a carcinogen.			
Chemical Name	ACGIH	IARC	NTP	OSHA	
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	А3	Group 2B		X	
Nickel		Group 2B	Reasonably Anticipated	X	

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity	No information available.		
STOT - single exposure	No information available.		
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).		
Chronic Toxicity	Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.		
Target Organ Effects	Respiratory system, Eyes, Skin, Gastrointestinal tract (GI). Central Vascular System (CVS). Kidney, Liver, Lungs, Heart.		
Aspiration Hazard	No information available.		

(d) Numerical measures of toxicity Product Information

The following values are calculated based on	ATEmix (oral):	
chapter 3.1 of the G <mark>HS document</mark>	ATEmix (dermal):	

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 10 / 15



RCRA - U Series

Wastes

11 / 15

RCRA - D Series

Wastes

www.cmczj-lab.com

Section 12-Ecological Information

(a) Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Section 13 – Disposal Considerations

Chemical Name

400-1668-320

•				
Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper	96h EC50: 0.031 - 0.054	96h LC50: 0.0068 - 0.0156		48h EC50: = 0.03
7440-50-8	mg/L (Pseudokirchneriella	mg/L (Pimephales romelas)		mg/L
	subcapitata) 72h EC50:	96h LC50: = 0.112 mg/L		
	0.0426 - 0.0535 mg/L	(Poecilia reticulata) 96h		
200	(Pseudokirchneriella	LC50: = 0.3 mg/L (Cyprinus		
	subcapitata)	carpio) 96h LC50: =		
		0.8mg/L (Cyprinus carpio)		
		96h LC50: = 1.25 mg/L		
		(Lepomis macrochirus) 96h		
		LC50: =0.052 mg/L		
		(Oncorhynchus mykiss) 96h		
		LC50: = 0.2mg/L		
	_	(Pimephales promelas)		
		96h LC50: < 0.3 mg/L		
1		(Pimephales promelas)		
Nickel	72h EC50: = 0.18 mg/L	96h LC50: > 100 mg/L		48h EC50: > 100
7440-02-0	(Pseudokirchneriella	(Brachydanio rerio) 96h		mg/L 48h EC50:
	subcapitata) 96h EC50:	LC50: = 1.3 mg/L (Cyprinus		= 1 mg/L
	0.174 - 0.311 mg/L	carpio) 96h LC50: = 10.4		
	(Pseudokirchneriella	mg/L (Cyprinus carpio)		/-
	subcapitata)			
(b) Persistence and Degradability	No information availal	ole.		
(c) Bioaccumulation	No information availal	ole		
(d) Other adverse effects	No information availal	ole.		

(a) Waste treatment methods Disposal methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements. Contaminated Packaging: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Nickel (hazardous constituent - Included in waste 7440-02-0 no waste number) streams: F006, F039

01&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China

info@cmczj-lab.com

RCRA - Basis for Listing

RCRA



California	Hazardous	Waste 6	Codes [•]	141
------------	------------------	---------	--------------------	-----

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste	
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	Toxic	
Copper 7440-50-8	Toxic	
Aluminum foil 7429-90-5	Ignitable powder	
Nickel	Toxic powder	
7440-02-0	Ignitable powder	

Section 14 – Transport Information		
(a) UN number	3480 & 3481	
(b) Proper shipping name	Lithium ion batteries (including lithium ion polymer batteries) (limited to a maximum of 30% SoC) or; Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion polymer batteries).	
(c) Label(s) / Placa <mark>rd</mark> Required:	Miscellaneous Lithium BATT	
	ns which a user needs to be aware of, or needs to comply with, in connection veyance either within or outside their premises	
ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IB, PI 966 Section II and PI 967 Section II appropriate of IATA DGR 65th (2024 Edition) for transportation.	
IMDG CODE:	The batteries are not restricted to IMDG Code 2022 Edition (Amdt 41-22) according to special provision 188.	
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.	
ADR/ ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2023.	

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 12 / 15



Section 15 - Regulatory Information

(a) International Inventories

TSCA: Complies.

DSL: All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

(b) US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 3 <mark>13 – Th</mark> reshold Values %
Lithium Cobalt Oxide (LiCoO ₂)	12190-79-3	37.47	0.1
Copper	7440-50-8	10.36	1.0
Aluminum foil	7429-90-5	9.25	1.0
Nickel	7440-02-0	1.34	0.1

SARA 311/312 Hazard Categories

3			
Acute Health Hazard	No		
Chronic Health Hazard	No		
Fire Hazard	No		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	x	
Nickel 7440-02-0		Х	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ
7440-50-8	3000 lb		RQ 2270 kg final RQ
Aluminum foil			
7429-90-5			
Nickel	100 lb		RQ 100 lb final RQ
7440-02-0	100 lb		RQ 45.4 kg final RQ

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 13 / 15



(c) US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65		
Nickel - 7440-02-0	Carcinogen		

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	X		X	x	X
Graphite 7782-42-5	X	Х	Х		
Copper 7440-50-8	X	Х	X	X	х
Aluminum foil 7429-90-5		Х		×	
Nickel 7440-02-0	X	X	Х	X	Х

(d) International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Graphit <mark>e</mark> 7782-4 <mark>2-5</mark>		Mexico: TWA= 2 mg/m3
Copper 7440-50-8		Mexico: TWA= 1 mg/m3 Mexico: TWA= 0.2 mg/m3 Mexico: STEL= 2 mg/m3
Aluminum foil 7429-90-5		Mexico: TWA 10 mg/m3
Nickel 7440-02- <mark>0</mark>		Mexico: TWA= 1 mg/m3

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 14 / 15




Section 16 - Additional Information

NFPA	Health Hazards	1	Flammability	0	Instability	0	Physical and Chemical Hazards	-
HMIS	Health Hazards	0	Flammability	0	Physical Hazard	0	Personal Protection	Х

Revision Note: No information available

Sample photo:



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

******End of report*****

 $\label{tensor} \mbox{Testing International (Shenzhen) Co., Ltd.}$

Address: 101&104, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping Community, Fuhai Street, Baoan District, Shenzhen, Guangdong, China

Tel: 400-1668-320 E-mail: info@cmczj-lab.com http://www.cmczj-lab.com

15 / 15