

**PRESENTS** 

## An Exciting New Innovation In Fishbox Waste Management



## New Generation of Fishbox Waste Evacuation

## Gulper Grouper Mk 3

Gulper Non-Choke Valve
Technology Valves prevent clogging

Valves prevent clogging (a common cause of motor burn out) Reliable -Heavy duty diaphragm for fishbox waste Quieter than typical macerators

360° rotating head

Low power consumption

Runs dry without damage

Ultimate debris handling

Simple Plumbing -Choice of 25mm (1") or 38mm (1 ½") hose connections

90° Connections -Ideal as a replacement for macerators in a fishbox installation Securing Strap -Holds pump in place in harsh marine conditions 2 Decades
of Marketing
Leading
Pump
Technology



## Fishbox Waste Management from Whale



| Model Specifications                                  |   |           |
|---|---|-----------|
| Model   | Gulper® Grouper Mk 3 Fishbox Discharge Pump with 90° head   |           |
| Product Code  | BP4772  | BP4774    |
| Voltage   | 12 V d.c.   | 24 V d.c. |
| Recommended Fuse Size<br>Automotive                   | 10 amp  | 5 amp     |
| Minimum Wire Size                                     | 1.5 mm² (16AWG)   |           |
| Weight  | 1.6 kg  | (3.5lbs)  |
| Hose Connections                                      | 25 mm (1") or 38 mm (1 ½")  |           |
| Materials   | Pump Body: Aluminium, Glass-filled Nylon<br>Clamp Ring: Acetal, Diaphragm: Santoprene®<br>Valves: Nitrile® Feet: EPDM, Gearwheel: Delrin<br>Fasteners: Stainless Steel, Brass |           |
| Materials in Contact with Fluid                       | Glass-filled Nylon, Santoprene®, Stainless Steel  |           |
| Maximum Suction Lift                                  | 1 m (   | 3.3 ft)   |
| Maximum Discharge Head                                | 2 m (6.5 ft)  |           |
| Maximum Discharge Head<br>and Suction Lift (combined) | 3 m (10 ft)   |           |
| Flow Rate per Minute                                  | 18 ltrs (4.74 US gals)  |           |
| Dry Running Current                                   | 4 amps  | 2 amps    |

| Performance Data     | BP4772 / BP4774                        |  |
|----------------------|--|--|
| Suction Lift         | 0                                      |  |
| Discharge Head       | 1 m (3 ft)                             |  |
| Flow Rate per Minute | 16 ltrs (4.22 US Gals)                 |  |
| Current Draw         | 6 amp (12 V d.c.)<br>3 amp (24 V d.c.) |  |

Contact Whale for further information or a free product demonstration

Whale, 2 Enterprise Road, Bangor, Northern Ireland, BT19 7TA Tel: +44 (0)28 9127 0531 info@whalepumps.com

whalepumps.com